



CAT6 U/UTP 23AWG 250Mhz

BC Bare copper Solid

	Blue-White/Blue	Orange-White/Orange
	Green-White/Green	Brown-White/Brow

ProductDetails

Conductor Material: Bare copper Construction: 23AWG;1/0.565±0.008mm Insulation Material: HDPE NormalThickness: 0.225mm Diameter: 1.03±0.05mm InnerLayer Direction: S PitchREF: 30mmunderneath OutsideLayer Direction: S PitchREF: 100±20mm Cross Material: Polyethylene Construction: 4.4mm×4.4mm Ripcord Material: Nylon Jacket Material: CM PVC Diameter:6.2±0.20mm Thickness:0.60mm(Min.Thickness:0.55mm)	Color WTGYBKRDYLGNBK Marking LAN Cable Category 6 U/UTP 23AWG/4PRS PVC VERIFIED TO EIA/TIA 568C & ISO/IEC 11801 METER Application
--	--

Product Characteristics

ELECTRICAL PROPERTIES

- **Insulation Resistance:** Min. 5000 mega ohms-km at 20C
- **Dielectric Test:** 1000V DC /1 min ; No Breakdown
- **Temperature Rating:** 60°C
- **Voltage Rating:** 30V

Certification standard

- independently tested and verified by ETL
- Guaranteed to meet TIA 568C.2 and ISO/IEC 11801 Specifications
- Center Cross Design
- Big Pulling Hole Design
- TIA 568C.2
- ISO 11801 CLASS E
- ETL approved
- UL listed

Packing



Lansan International Limited

Tel: (86)755-84292700 /84292800

Address: B3 Building, 99 Tong Xin Industrial Park, Tong Xin Road,
Tongle County, Longgang District, Shenzhen, Guangdong,
China, 518116

Website: <http://www.lansan-cabling.com/>
<http://lansuncable.en.alibaba.com/>

